



Perodua Kelisa Specifications

Engine	EJ-VE petrol, transverse, water cooled, in-line 3 cylinder, DOHC, 12 valve with VVT	
Bore/stroke	72 x 81 mm	
Capacity	989 cc	
Max Power	55PS (40.5kW) at 5,200 rpm	
Compression ratio	10.0:1	
Max Torque	88.3 Nm at 3,600 rpm	
Fuel System	Electronic sequential fuel injection	
Transmission	Manual 5-speed	Automatic 3-speed
1st	3.417	2.731
2nd	1.947	1.526
3rd	1.250	1.000
4th	0.865	
5th	0.707	
Reverse	3.143	2.290
Final Drive	3.938	3.966
Clutch	Dry single plate with diaphragm spring	
Suspension		
Front	Independent MacPherson strut, coil springs, anti-roll bar	
Rear	Semi-trailing arm with 3-link location, coil springs, beam axle	
Brakes	Solid front discs/rear drums with servo assistance	

Steering

Type	Rack and pinion with power assistance
Turning circle	4.6 metres

Wheels/tyres

4.5J with 155/65R13

Economy

	Manual 5-speed	Automatic 3-speed
Urban (mpg)	44.1	36.7
Extra-urban (mpg)	64.2	48.7
Combined (mpg)	55.4	43.5
CO2 (g/km)	121	153
Fuel tank capacity	40 litres	
Load capacity	155/426 litres VDA	

Performance

	Manual 5-speed	Automatic 3-speed
0-60 mph	14.8 secs	17.2 secs
Top Speed	88 mph	87 mph

Dimensions

Length	3490 mm
Width	1490mm
Height	1420 mm
Interior length	1720 mm
Interior width	1220 mm
Interior height	1170 mm
Wheelbase	2345 mm
Track front	1310 mm
Track rear	1280 mm
Min ground clearance	130 mm
Kerb weight	EX 760kg, GX 760kg, EZ 770kg
Gross vehicle weight	1270 kg

Warranty

2 year, 24,000 miles,
6-year anti-perforation
1 year road side assistance

Insurance Group

3A

John Childs (Garages) Ltd,
Bridge Road,
Brabourne Lees,
Kent, TN25 6QQ

Tel: 01303 812727

www.john-childs.co.uk